CROSSFIRE E1





CROSSFIRE

12.4kw/H Electric ATV

IMAGES







DESCRIPTION

One of the world's first true 4WD electric UTV vehicles. With low and high range and fully regenerative braking.

The E1 is the easiest to use UTV as the power is effortless the brakes are regenerative so as you slow down the engine captures the power and recharges the batteries.

The onboard charger is simply a matter of plugging into the wall socket with a charge time of around

The 48 Volt 38 HP AC drive train is powerful enough to go over the toughest terrain without all the noise of a gas-powered engine. Nitrogen-Assisted Independent Suspension and Four-Wheel Hydraulic

> 100% Electric 100% Torque off the line 100% No emissions during use 100% Quiet

Brakes will keep you in full control. Built for stability and performance.

The E1 is the easiest to use UTV as the power is effortless the brakes are regenerative so as you slow down the engine captures the power and recharges the batteries.

The onboard charger is simply a matter of plugging into the wall socket with a charge time of around 6 hours.

It does not matter if you are in hospitality and need silence and ability to access all points in hotel without disturbing the guests or you are using the E1 to get around the shopping centre car park.

How about event managers getting around site. Or security companies needing all-terrain vehicles without disturbing the peace?

Now did we mentions the councils wanting to show environmental credentials while not losing the true nature of needing a reliable rugged Utility vehicle? 100% Electric 100% Torque off the line

100% No emissions during use 100% Quiet

Type

SPECIFICATIONS

Motor **AC Induction** Controlled by Sevcon Gen4(tm) Speed controller **Battery Voltage** 48VDC 12.4kw/H Horsepower 27Hp Torque (ft. lbs.) 220 **Number of Motors Battery Type** Discover™ Dry Cell **Battery Capacity** 2080 Amp/Hours Charge Time 6 - 8 hours **Final Drive Shaft Drive Charging System** On-Board Charger Delat Q Drivetrain Transmission Automatic **Drive System modes** Low Range 100% Torque High Range 70% Torque Max Distance 50% Torque **Max Speed** 40km/h Range >70Km

Chassis / Suspension / Brakes

Suspension Front Independent Dual A-arm / & Rear Nitrogen Filled **Brakes Front & Rear Dual Ventilated Hydraulic Disc**

Selectable 2WD/4WD

2800mm x 1580mm x 1840mm

Tyres Front: AT26 x 9 -14 Radial Rear: AT26 x 11 -14 Radial

Dimensions

Height

Length x Width x

4x4 Mode

Wheelbase 186cm **Empty Weight** 830KG Cargo Bed Capacity 200Kg 389Kg Level ground **Towing Capacity** 227Ka 15 dearee 68 Kg Tow ball vertical load limit 15km/h To speed limit

Ground Clearance 10'

Dimensions

Instrumentation Digital-Analog Display

Warranty 2-Year Manufacturer Warranty

Accessories:

- 3500 lb Winch
- Roof
- Windshield

- Aluminium Rims
- Turn Signals
- Gas Assisted Adjustable Shocks

